



TAFE 240 S

Classic lines with modern technology



With its 50 hp and three-cylinder engine with 2600 cubic centimetres, the TAFE 240S delivers enough power for various agricultural tasks. Its timeless, simple design combines functionality with clean lines and allows for easy operation in all applications. The transmission with eight forward and two reverse gears flexibly adapts to different operating conditions, while the IPTO PTO and Split Torque clutch facilitate the operation of various attachments. With a lifting capacity of 1450 kilograms, the tractor is also suitable for heavier work and overall offers functional and reliable equipment for daily use.



TAFE 240 S

Classic lines with modern technology



Length	3707 mm
Minimum width*	1765 mm
Height*	2670 mm
Wheelbase	1935 mm
Ground clearance*	264 mm
Curb weight	2290 kg
Turning radius (outside)*	3798 mm
max. axle load at the front	1070 kg
Max. axle load rear	2200 kg
permissible. Total weight	3300 kg
Towing capacity unbraked	1300 kg
Towing capacity braked	4000 kg
Manufacturer	Simpson & Co. Ltd.
Type	Water-cooled 3-cylinder 4-stroke diesel
Model series	SJV326CR49-2
Injection	Common Rail Direct Injection
Engine power	49.5 hp
Number of cylinders	3
Speed	2200 rpm
Displacement	2600 cc
Air filter	Dry air filter
Battery Volt	12 Volt
Gearbox Type	Manual transmission
Steps / Corridors	8F+2R
Maximum speed*	27 km/h
Clutch	Dry clutch
Steering	Hydraulic
Tank capacity	55 l
Hydraulic System Pump	Piston Gate Pump "Scotch Yoke"
Hydraulic system working hydraulics	41 l/min
Hydraulic System Servo	21 l/min
Three-point hitch	Category 1
Lifting capacity rear linkage	1450 kg
Regulation	Position-Position and Traction Control, Mechanical
Additional control unit	1x double-acting rear
Rear PTO	540 rpm
Driven wheels	2WD (rear-wheel drive)
Standard equipment	Drawbar, Telescopic lower link supports, Oil bath brakes, Standard lights, Seat with seat belt, Vehicle equipment according to StVZO
Standard tyres type	Ackerstollen Diagonal
Standard front tyres	6.00-16
Standard rear tyres	13.6-28

* Depending on tyres, measured with specified standard tyres



Comvex Agri LTD.
Pottery Road, Low Southwick
Sunderland SR5 2BP
Tel: 0191 548 2828
Email: enquiries@machinerydealer.co.uk