



TAFE 6028 M/H

Compact performance
for every application



Compact, but by no means small: The TAFE 6028 series convinces with real tractor performance in a handy format. With 25 hp, a powerful 3-cylinder mitsubishi engine and 739 kg lifting power at the rear, the 6028 is ideal for working on the farm, in horticulture and landscaping or in the municipal sector. With 26 l/min working hydraulics, an empty weight of over 1000 kg, standard arable rail and switchable all-wheel drive, the 6028 models offer everything that counts in daily use.

Two variants are available:

- The TAFE 6028M with classic 9F + 3R manual transmission reaches up to 25 km/h and offers a direct driving experience.
- The TAFE 6028H with hydrostatic drive allows sensitive advance and retraction with a double pedal. This is ideal for mowing in conjunction with the standard central axis pto shaft.





TAFE 6028 M/H

6028H

Engine

Power: 25 HP

Lifting capacity: 739 kg

Gearbox

Hydrostatic

Gears: 3 speed H-M-L

6028M

Engine

Power: 25 HP

Lifting capacity: 739 kg

Gearbox

Manual transmission

Gears: 9F + 3R



	6028H	6028M
Length		3135 mm
Minimum width*		1100 mm
Height*		2310 mm
Wheelbase		1550 mm
Ground clearance*		260 mm
Empty weight	1100kg	1095 kg
Turning radius (outside)*		2440 mm
Track in front*		928 mm
Track width in the back*		888mm
Max. axle load in front		600 kg
Max. axle load rear		1000 kg
zul. Total weight		1600 kg
Towing load unchecked	320 kg	950 kg
Towbar braked		2500 kg
Manufacturer		Mitsubishi
Type		Water-cooled 3-cylinder 4-stroke diesel
Model series		MVS3L2
Injection		Indirect
Engine power		25 hp
Number of cylinders		3
Speed		2600 rpm
Displacement		1319 ccm
Air filter		Dry air filter with blockage indicator
Battery Volt		12 Volt
Gearbox Type	Hydrostat	Manual transmission
Steps / Aisles	3 steps	9F+3R
Top speed*	19 km/h	25 km/h
Coupling		Single disc dry coupling 200mm
Steering		Hydraulic
Tank capacity		23l
Hydraulic system pump		2 Gear pumps
Hydraulic system working hydraulics		26 l/min
Hydraulic system Servo		16 l/min
Three-point suspension		Category 1
Lifting force rear force lifter		739 kg
Regulation		Position+train resistance
Additional control unit		1x double acting
Pto Switching		Mechanical
Pto mid	2000 rpm	
PTO shaft in the rear	540 rpm	540/54DE (750) RPM
Driven wheels		4(2 and 2 switchable)
Standard Tyre Type		Arable studs diagonal
Standard tyres in front		180/85012
Standard rear tyres		8.3-20

* Depending on tyres, measured with specified standard tyres



Convex Agri LTD.
Pottery Road, Low Southwick
Sunderland SR5 2BP
Tel: +44 (0) 191 548 2828
Email: enquiries@machinerydealer.co.uk